



STANLEY

Wide range of models to suit varied duties
In-transit charging kit
Speeds loading and delivery
Operates on tight landings
Eliminates product and premises damage

Minimises physical effort and strain
Extensive certificated training available
Preventive maintenance schedule available
Conform to EC handling regulations

Suitable for a variety of applications including:

Commercial catering equipment, couriers/delivery services, fire cabinets, lifts & elevators, mainframe computers, motors, pool tables, pumps, rail industry, security & safes, shops/retail, switchgear frames, vending & licenced trade, white goods

M1

- Maximum Capacity 680kg
- Maximum Height Deck/Dock 840mm
- Weight 75kg
- Toe Plate 610x150mm
- Overall Width (WxDxH) 685x430x1520mm
- Electronic Charger 220/240V 4amp
- Truck Construction Steel
- Wheels 200mm / Rubber Solid
- Gel Filled Leak Proof Battery 12V – 30 amp



M2B

- Maximum Capacity 680kg
- Maximum Height Deck/Dock 840mm
- Weight 82kg
- Toe Plate 685x150mm
- Overall Width (WxDxH) 685x430x1730mm
- Electronic Charger 220/240V 4amp
- Truck Construction Steel
- Wheels 200mm / Rubber Solid
- Gel Filled Leak Proof Battery 12V – 30 amp

